


07. May 2021

DALLMER**floor drain DallDrain Select vertical, DN 50/DN 100, 100 x 100 mm**

Product No. **517135**
 EAN: 4001636517135
 Discount group: 6



conforming to DIN EN 1253
 Floor drain including grating DallDrain Select with stainless steel grate in stainless steel frame. Outlet DN 50/DN 100 vertical.

specification

- Stainless steel grate and frame
- Integrated screed anchoring
- Flexible, click-in sealing sleeve for secure connection to bonded and sheet waterproofing conforming to DIN 18534
- Fully removable, two-piece trap insert and rodding eye, 50 mm water seal (conforming to DIN EN 1253)
- Temporary blanking plate
- Three sound-insulated mounting feet for fixing and height adjustment 47 – 250 mm
- Spigot can be shortened for floorings 10 – 36 mm (including adhesive)

MATERIAL

Polypropylene drain body and outlet, highly impact-resistant; 1.4301 stainless steel grate, load class K 3 (300 kg); spigot in ABS, frame in 1.4301 stainless steel

Pre-assembled set consisting of parts no. 517265 + 517234 + 517340.
 Grating with positioning aid laterally adjustable +/- 2.5 mm.

Can be used with fire and sound-insulating collar - installation kit 2 (part no. 515025) or fire protection kit 12 (part no. 515438).

Product No.	Description	Dimensions
517340	DallDrain installation feet	